

54FCT541

Octal Buffer/Line Driver with TRI-STATE® Outputs

General Description

The 'FCT541 is an octal buffer and line driver with TRI-STATE outputs designed to be employed as a memory and address driver, clock driver, or bus-oriented transmitter/receiver. The 'FCT541 is similar to the 'FCT244 with broad-side pinout.

Features


- Non-inverting buffers
- TTL input and output level compatible
- CMOS power consumption
- Output sink capability of 48 mA, source capability of 12 mA
- Flow-through pinout for ease of PC board layout
- Standard Microcircuit Drawing (SMD) 5962-8976601

Ordering Code


Military	Package Number	Package Description
54FCT541DMQB	J20A	20-Lead Ceramic Dual-In-Line
54FCT541FMQB	W20A	20-Lead Cerpack
54FCT541LMQB	E20A	20-Lead Ceramic Leadless Chip Carrier, Type C

Connection Diagram

Pin Assignment
DIP and Cerpack



Pin Assignment
LCC



Pin Names	Description
$\overline{OE}_1, \overline{OE}_2$	Output Enable Input (Active Low)
I_0-I_7	Inputs
O_0-O_7	Outputs

Inputs			Outputs
\overline{OE}_1	\overline{OE}_2	I	FCT541
L	L	H	H
H	X	X	Z
X	H	X	Z
L	L	L	L

H = HIGH Voltage Level
L = LOW Voltage Level
X = Immaterial
Z = High Impedance

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/ Distributors for availability and specifications.

Storage Temperature	–65°C to +150°C
Ambient Temperature under Bias	–55°C to +125°C
Junction Temperature under Bias	
Ceramic	–55°C to +175°C
V _{CC} Pin Potential to	
Ground Pin	–0.5V to +7.0V
Input Voltage (Note 2)	–0.5V to +7.0V
Input Current (Note 2)	–30 mA to +5.0 mA
Voltage Applied to Any Output	
in the Disabled or	
Power-Off State	–0.5V to 5.5V

in the HIGH State	–0.5V to V _{CC}
Current Applied to Output	
in LOW State (Max)	twice the rated I _{OL} (mA)
DC Latchup Source Current	–500 mA

Recommended Operating Conditions

Free Air Ambient Temperature	
Military	–55°C to +125°C
Supply Voltage	
Military	+4.5V to +5.5V
Minimum Input Edge Rate	(ΔV/Δt)
Data Input	50 mV/ns
Enable Input	20 mV/ns

DC Electrical Characteristics

Symbol	Parameter	FCT541			Units	V _{CC}	Conditions
		Min	Typ	Max			
V _{IH}	Input HIGH Voltage	2.0			V		Recognized HIGH Signal
V _{IL}	Input LOW Voltage			0.8	V		Recognized LOW Signal
V _{CD}	Input Clamp Diode Voltage			–1.2	V	Min	I _{IN} = –18 mA
V _{OH}	Output HIGH Voltage	54FCT	4.3		V	Min	I _{OH} = –300 μA
		54FCT	2.4		V	Min	I _{OH} = –12 mA
V _{OL}	Output LOW Voltage	54FCT		0.2	V	Min	I _{OL} = 300 μA
		54FCT		0.55	V	Min	I _{OL} = 48 mA
I _{IH}	Input HIGH Current			5	μA	Max	V _{IN} = V _{CC}
I _{IL}	Input LOW Current			–5	μA	Max	V _{IN} = 0.0V
I _{OZH}	Output Leakage Current			10	μA	Max	V _{OUT} = 5.5V; \overline{OE}_n = 2.0V
I _{OZL}	Output Leakage Current			–10	μA	Max	V _{OUT} = 0.0V; \overline{OE}_n = 2.0V
I _{OS}	Output Short-Circuit Current			–60	mA	Max	V _{OUT} = 0.0V
I _{CCQ}	Quiescent Power Supply Current			1.5	mA	Max	V _{IN} < 0.2V or V _{IN} 5.3V, V _{CC} = 5.5V
ΔI _{CC}	Quiescent Power Supply Current			2.0	mA	Max	V _I = V _{CC} – 2.1V
I _{CCD}	Dynamic I _{CC}			0.4	mA/ MHz	Max	V _{CC} = 5.5V, Outputs Open, One Bit Toggling, 50% Duty Cycle, \overline{OE}_n = GND
I _{CC}	Total Power Supply Current			6.0	mA	Max	V _{CC} = 5.5V, Outputs Open, f _I = 10MHz, \overline{OE}_n = GND, One Bit Toggling, 50% Duty Cycle, \overline{OE}_n = GND

Note 1: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

AC Electrical Characteristics


Symbol	Parameter	54FCT		Units	Fig. No.
		T _A = −55°C to +125°C V _{CC} = 4.5V–5.5V C _L = 50 pF			
		Min	Max		
t _{PLH}	Propagation Delay	2.0	9.0	ns	Figure 4
t _{PHL}	Data to Outputs	2.0	9.0		
t _{PZH}	Output Enable Time	2.0	12.5	ns	Figure 5
t _{PZL}		2.0	12.5		
t _{PHZ}	Output Disable Time	2.0	12.5	ns	Figure 5
t _{PLZ}		2.0	12.5		

Capacitance

Symbol	Parameter	Max	Units	Conditions $T_A = 25^{\circ}\text{C}$
C_{IN}	Input Capacitance	10.0	pF	$V_{CC} = 0.0\text{V}$
C_{OUT} (Note 3)	Output Capacitance	12.0	pF	$V_{CC} = 5.0\text{V}$

Note 3: C_{OUT} is measured at frequency of $f = 1\text{ MHz}$, per MIL-STD-883B, Method 3012.

AC Loading



*Includes jig and probe capacitance

FIGURE 1. Standard AC Test Load




FIGURE 2. Test Input Signal Levels

Amplitude	Rep. Rate	t_w	t_r	t_f
3.0V	1 MHz	500 ns	2.5 ns	2.5 ns

FIGURE 3. Test Input Signal Requirements

AC Waveforms




FIGURE 4. Propagation Delay Waveforms for Inverting and Non-Inverting Functions






FIGURE 5. TRI-STATE Output HIGH and LOW Enable and Disable Time

Physical Dimensions inches (millimeters) unless otherwise noted



E20A (REV D)


20-Terminal Ceramic Chip Carrier
NS Package Number E20A



J20A (REV M)

20-Lead Ceramic Dual-In-Line Package
NS Package Number J20A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



20-Lead Ceramic Flatpack
NS Package Number W20A

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
Americas
Tel: 1-800-272-9959
Fax: 1-800-737-7018
Email: support@nsc.com

www.national.com

National Semiconductor Europe

Fax: +49 (0) 1 80-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 1 80-530 85 85
English Tel: +49 (0) 1 80-532 78 32
Français Tel: +49 (0) 1 80-532 93 58
Italiano Tel: +49 (0) 1 80-534 16 80

National Semiconductor Asia Pacific Customer Response Group

Tel: 65-2544466
Fax: 65-2504466
Email: sea.support@nsc.com

National Semiconductor Japan Ltd.

Tel: 81-3-5639-7560
Fax: 81-3-5639-7507